

Ocean LED light/ Foco Ocean


The **Ocean submersible LED light** is the result of our constant search for excellence. Lighting available in 36W LED High performance, optional RGB, RGBW and WHITE, also 10° or 30° lenses, IP 68 connector included. Manufactured in brass and Stainless Steel AISI-304, **new slim design, is strong and very light, IP68 certified**. High heat dissipation, thanks to the large contact area.

El **foco LED sumergible Ocean** es el resultado de nuestra continua búsqueda de la excelencia. Iluminación disponible en 36W de potencia LED de alto rendimiento y opcional RGB, RGBW, BLANCO, y ópticas 10° o 30°, conector incluido. Fabricado en Latón y Acero Inoxidable AISI-304, **diseño extraplano, es un foco robusto, muy ligero y certificado IP 68**. Alta disipación de calor, gracias a la gran superficie de contacto.



Certifications/ Certificaciones

IP68 CE



Light charts/ Gráficos de iluminación.

Spot/ Intensivo (Beam 10°)							Flood/ Extensivo (Beam 30°)						
Color	500 White/ Blanco		250 RGB		750 RGBW		Color	500 White/ Blanco		250 RGB		750 RGBW	
Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro
1 m	Ø 0,22	16808 lx	Ø 0,18	12063 lx	Ø 0,20	13428 lx	1 m	Ø 0,54	10171 lx	Ø 0,51	6095 lx	Ø 0,53	9336 lx
2 m	Ø 0,42	4202 lx	Ø 0,36	3016 lx	Ø 0,39	3357 lx	2 m	Ø 1,06	2543 lx	Ø 0,99	1524 lx	Ø 1,02	2334 lx
3 m	Ø 0,60	1867 lx	Ø 0,52	1340 lx	Ø 0,55	1492 lx	3 m	Ø 1,56	1130 lx	Ø 1,44	677 lx	Ø 1,50	1037 lx
4 m	Ø 0,81	1050 lx	Ø 0,70	754 lx	Ø 0,74	839 lx	4 m	Ø 2,11	636 lx	Ø 2,02	381 lx	Ø 2,09	583 lx
5 m	Ø 0,97	672 lx	Ø 0,87	482 lx	Ø 0,92	537 lx	5 m	Ø 2,64	407 lx	Ø 2,57	244 lx	Ø 2,59	373 lx
6 m					Ø 1,07	373 lx	6 m					Ø 3,18	259 lx

Electrical data/ Datos eléctricos

Details/ Detalles

Reference/ Referencia	Model/ Modelo	Power/ Potencia	Voltage/ Voltaje	Beam angle/ Ángulo	Color/ Color	LEDs Num./ Nº de LEDs	Lumens/ Lúmens	Life span/ Vida útil	Material/ Material	Weight/ Peso	Elect. connection/ Conexión eléctrica		
F5220202	500	36 W	24V DC	10°	White 6500K	12	1524 lm	40000/hrs	STAIN- LESS STEEL AISI-304 - BRASS/ ACERO INOXID- ABLE AISI-304 - LATÓN	1,63 kg	Plug & Socket / Conector enchufable IP68 Connector H05RR-F/ H05RN-F H07RR-F/H07RN-F Ø 7 - Ø12		
F5220213				30°			1524 lm						
F5225207	250	20 W		10°	RGB		930 lm						
F5225218				30°			930 lm						
F5216218	750	36 W		10°	RGBW		2448 lm				3m H07RN-F 5G1mm²		
F5216229				30°			2448 lm						

Further information at www.saferain.com | Más información en www.saferain.com